



VONMARCKEN
LABORATORY & MEDICAL EQUIPMENT

Klik hier voor meer informatie op vonmarcken.nl

Thermo Scientific Cryogenic Chest Freezers

Ultra-low temperatures for ultra-reliable sample protection.



More convenient than LN₂

- Designed for long-term biological storage at uniform temperatures of -140°C and -150°C without LN₂ as a cooling medium
- Eliminates the need for maintaining a supply of LN₂
- 100% of the interior space is usable, with stored samples maintained below critical temperatures
- Ample interior volume with capacity of up to 21,600 samples in model ULT-10140 and up to 14,400 samples in model ULT-7150 (2mL vials in boxes)

Specially designed refrigeration system

- Single compressor, orbital refrigeration system designed for cryogenic storage
- Specially mixed, CFC/HCFC-free refrigerants maximize cooling and minimize environmental impact

- Downfeed evaporator provides efficient refrigerant flow for a higher system efficiency and a better cabinet temperature uniformity
- Washable condenser filter keeps fins free of dust to maintain peak cooling efficiency; no tools required for removal
- Comes standard with RS232 output and access port on rear of unit

Advanced control features

- Microprocessor control system with touchpad data entry and digital display allows for intuitive operation
- Set point security system for main power and alarm locks in temperature and alarm set points for increased sample protection
- Incident monitor provides visual and audible warnings of system abnormalities for increased sample protection



Thermo Scientific Cryogenic Chest Freezers (Operating Temperature -140°C)

Model No.	Capacity cu. ft. (L)	Electrical	Amps/Breaker (Plug)	Interior Dimensions* H x D x W in. (cm)	Exterior Dimensions* H x D x W in. (cm)	Shipping Weight lbs. (kg)
ULT-10140-9-D	10.3 (292)	208/230 V, 60 Hz 1Ø	23/30 (P6)	26.5 x 19 x 35.25 (67.4 x 48.3 x 89.5)	42.75 x 29 x 69 (108.6 x 73.7 x 175.3)	1065 (483)
ULT-10140-9-M		380 V, 50 Hz 3Ø	11/15 (HW) ¹			
ULT-10140-9-V		220/240 V, 50 Hz 1Ø	23/30 (HW) ¹			

Thermo Scientific Cryogenic Chest Freezers (Operating Temperature -150°C)

Model No.	Capacity cu. ft. (L)	Electrical	Amps/Breaker (Plug)	Interior Dimensions* H x D x W in. (cm)	Exterior Dimensions* H x D x W in. (cm)	Shipping Weight lbs. (kg)
ULT-7150-9-D	6.8 (193)	208/230 V, 60 Hz 1Ø	23/30 (P6)	26.5 x 19 x 23.5 (67.4 x 48.3 x 59.7)	42.75 x 29 x 58 (108.6 x 73.7 x 147.4)	825 (374)
ULT-7150-9-M		380 V, 50 Hz 3Ø	11/15 (HW) ¹			
ULT-7150-9-V		220/240 V, 50 Hz 1Ø	23/30 (HW) ¹			

* All dimensions and specifications are subject to change without notice. External dimensions include allowances for cabinet door, hinges, latches, handles and control panel protrusions.
¹. No plug provided, required hardware connection by customer

Thermo Scientific Racking Systems

Model No.	Description	Dimensions in. (cm)	2" Boxes/Rack	Racks/Freezer 10.3 cu. ft. (292L)	Racks/Freezer 6.8 cu. ft. (193L)
398186	2" cryo box rack	5.5 x 26.5 x 5.5 (14 x 67.3 x 14)	12	18	12
398187	3" cryo box rack	5.5 x 26.5 x 5.5 (14 x 67.3 x 14)	8	18	12
398188	27-position microplate rack	5.3 x 25.8 x 3.6 (13.5 x 65.5 x 9)	N/A	30	20

Optional Chart Recorders

Model No.	Description
Chart Recorder: 6" (15 cm), 7-Day Circular, Inkless	
6183-5	Factory installed, built-in chart recorder
6383-5A	Field installed,** free-standing chart recorder, 115V / 60Hz
6383-5D	Field installed,** free-standing chart recorder, 208-230V / 60Hz
6383-5V	Field installed,** free-standing chart recorder, 230V / 50Hz, EU plug
6383-5W	Field installed,** free-standing chart recorder, 230V / 50Hz, U.K. plug
7289	Chart recorder paper (package of 50, temp. range: 0°C to -200°C)

Optional Back-Up Systems

Model No.	Description
LN2 Back-Up System	
6595	Factory installed
6214-1	Field installed,** 115V / 60Hz, NEMA 5-20 plug
6214-8	Field installed,** 208-220V / 60Hz, NEMA 6-15 plug
6214-13	Field installed,** 230V / 50Hz, EU plug
6214-21	Field installed,** 230V / 50Hz, U.K. plug

Optional Accessories

Model No.	Description
4425C	Cryo gloves, medium
4426C	Cryo gloves, large

Optional Smart-View™ Wireless Monitoring Solution

Our optional Thermo Scientific Smart-View wireless monitoring solution safeguards sample integrity by continuously monitoring critical parameters and securely logging data to give you peace of mind. For more information, visit www.thermoscientific.com/smart-view.

** Must be installed by a qualified professional.  CE mark available only on 380V and 220/240V models

www.thermoscientific.com/cold

© 2013 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

Australia +61 39757 4300
Austria +43 1 801 40 0
Belgium +32 53 73 42 41
China +86 21 6865 4588 or
+86 10 8419 3588
France +33 2 2803 2180
Germany national toll-free 0800 1 536 376
Germany international +49 6184 90 6000

India toll free 1800 22 8374
India +91 22 6716 2200
Italy +39 02 95059552
Japan +81 45 453 9220
Netherlands +31 76 579 55 55
New Zealand +64 9 980 6700
Nordic/Baltic/CIS Countries
+358 9 329 10200

Russia +7 812 703 42 15
Spain/Portugal +34 93 223 09 18
Switzerland +41 44 454 12 22
UK/Ireland +44 870 609 9203
USA/Canada +1 866 984 3766 (866-9-THERMO)

Other Asian Countries +852 2885 4613
Countries not listed: +49 6184 90 6000

Thermo
SCIENTIFIC
Part of Thermo Fisher Scientific