



HOSHIZAKI

1-DOOR REFRIGERATED CABINET, HC PREMIER K W80 L DR

Product Serie: Premier

Artikelnummer: 171801010



The Hoshizaki PREMIER is a series of heavy-duty cabinets for energy-efficient refrigeration (Climate Class 5), catering to the needs of gastronomic perfectionists. The durable design with solid door hinges, stable stainless steel, and flawless finish is built to withstand the most demanding kitchen operations. The low-height PREMIER cabinets are customizable with castors instead of legs to easily fit into low-ceiling environments, yet convince with a surprisingly high internal volume. The Premier K W80 L DR is a 1-Door Refrigerated Cabinet, HC with a net internal volume of 475. The dimensions are 810 x 800 x 2080-2130 mm.

"FOOD SAFETY & TEMPERATURE STABILITY

The efficient air circulation system helps to maintain perfect storage temperatures and to recover the inside temperature rapidly after each door opening and defrosting. Additionally, the automatic defrost function ensures stable temperatures at all times. The wide, magnetic gaskets provide an effective seal and reduce escaping of cold air.

COMPARTMENTALIZED DESIGN The PREMIER's condenser is positioned on top of the cabinet, which brings multiple advantages. The cabinets can be hosed down in one run, without risking electric shortcuts. As the evaporator is positioned on top of the cabinet, valuable space inside the cabinet can be used for storage. Additionally, it can easily be serviced via the front flap on top of the cabinet.

LOW RUNNING COSTS & SUSTAINABILITY

The energy-efficient refrigeration technology implemented in this broad line-up of storage cabinets can help save running costs on an everyday basis. The Premier K W80 L DR runs on natural refrigerant and has [5].

ERGONOMIC & EASY TO USE

Extras, like the practical pedal-foot door opener, allow hands-free opening, contribute to a healthier work environment, and are a real-time-saver for hectic kitchen operations. The functional and intuitive display is easy to understand and use.

HYGIENE & WASTE REDUCTION

Thanks to the rounded corners, smooth surfaces, and molded rails, frequented cleaning routines become a quick and simple task. The practical anti-tilting function prevents spillage. The Interior and exterior are made of AISI 304 stainless steel and are perfectly suitable for humid locations.

EASY CUSTOMIZATION & FLEXIBILITY PREMIER

cabinets can easily be adjusted to your requirements, for example, the length of the legs, the position of the door, and the foot pedal. They also can accommodate shelves up to 18-22 levels (4 shelves included) offering you high flexibility to accommodate different types of produce. "

SPECIFICATIES

Productnaam	1-Door Refrigerated Cabinet, HC	Energie verbruik Ecodesign (kWh/Jaar)	337
Temperatuurbereik	+2/+12°C	Energie Efficiëntieklasse (ISO 22041-2019)	A
Inhoud, bruto (liter)	700	Energie Efficiëntie Index EEI	24.29
Netto bruikbaar volume (liter)	475	Geluidsniveau – dB(A)	46
Uitwendig	RvS AISI 304	Klimaatklasse	5
Inwendig	RvS AISI 304	Poten / Wielset	H = 130/180 mm (L)
Afmetingen W x D x H (mm)	810 x 800 x 2080-2130	Koelmiddel (kg)	0.08
Gewicht, verpakt (kg)	135	CO2 Equivalent (kg)	0.24
Isolatie (mm)	80 mm (polyurethane)	GN – Shelf size	2/1 GN Breed
Koelmiddel	R600a	Maximaal aantal roosters	18, distance of 71 mm
GWP	3	Aantal roosters	4
Koelcapaciteit bij -10°C (Watt)	206	Uitgerust met	Rechtsdraaiende omkeerbare deur met slot, automatische deursluiting, pedaaldeuropener, 4 grijze roosters, LED-verlichting
Aansluiting	230V, 50 Hz	Deur type	Geïsoleerde deur
Aansluitwaarde (Watt)	120		