



Best overview through glass door
Granted the viewing of the measured facilities.



Cable pass-through
The cable pass-through in the right side wall (7 cm diameter) allows easy connection to devices.

LABO-720- CHROMAT



- **External housing** made from galvanised sheet steel (rust-proof), with white, anti-scratch powder coating. Length of the plug cable: approx. 3 m.
- **Adjustable feet** to compensate uneven floors.
- **Interior** made from smooth aluminium with colourless protective coating. Gibs (every 15 mm) for flexible interior arrangement.
- **Interior consists** of five plastic-coated shelves on overlays.
- **Extra-thick 70 mm energy saving insulation**, made from high-quality, compression-moulded and environmentally friendly material.
- **Self-closing glasdoor** with easy-to-replace plastic magnetic seal frame, lockable.
- **Door hinge** on the right-hand side (by default, see illustration), or the left-hand side, can be retrofitted.
- **Forced-air cooling** with cross-flow blower, switches off automatically when you open the door, ensures a uniform temperature and minimizes temperature deviations.
- **LED-Illumination** mounted on side wall. Permanent lighting can be switched-on over a button at the control panel.
- **3 moisture-proof sockets** mounted in the interior.
- **The cable pass-through** in the right side wall (7cm diameter) allows easy connection to devices.
- **Automatic fast defrosting** thanks to time-limited and temperature-monitored reversal of the refrigerant circuit.
- **Condensate evaporates** in stainless steel heated dish beneath the refrigerator floor.
- **Key switch** protected control panel against tampering. Membrane keyboard with digital temperature display and minimum/maximum temperature memory.
- **Warning functions** with visual and audible alarm signal in the case of temperature deviations or other malfunctions. Door open alarm after 60 seconds.
- **Alarms** can be forwarded using a potential-free contact (e.g., to a mobile phone with optional GSM-Module or to a control centre).
- **RS485 interface** for connecting to PC-supported temperature documentation (using the optional KIRSCH-PC-KIT).
- **Antifreeze** against sub-zero temperatures.
- **Ventilation-enforced refrigerating machine**, hermetically sealed, energy saving, low-noise, easy to service.
- **Low-noise compressor** reduces noise by 10 dB to 40 dB (corresponds to noise level I; sound perception: whisper).

Specification

Capacity	700 litres
Temperature setting	approx. +4 °C to +20 °C
Voltage	220 – 240 V, 50/60 Hz
Power consumption	370 watts
Normal consumption	3.00 kWh/24 h
Admissible ambient temperature	from +10 °C to +38 °C
Heat emission (max.)	453 watts
Exterior dimensions (including door handle and distance from wall)	w x d x h = 77 x 98 x 193-196 cm
Interior dimensions	w x d x h = 62 x 77 x 140 cm (usable width 2 cm, usable depth 11 cm, usable height 13 cm less)
Exterior dimensions with door open at 90°	w x d = 77 x 165 cm
Shelf size	w x d = 59 x 65 cm
Max. load shelf	40 kg
Weight	Net weight 145 kg, gross weight 180 kg

Optional equipment

- **Power failure alarm** (visual and audible alarm), the monitoring unit remains in operation for approx. 72 hours on battery power.
- **Equipped with castors.**
- **Water-cooled refrigerating machine.**
- **Housing made of stainless steel 4301**, longitudinal brushed.
- **Aluminium-drawer on roller runners**
w x d x h = 56 x 60 x 10 cm (a maximum of eight drawers is possible).
- **Additional length and cross dividers** (for drawer).
- **Stainless steel drawer** (liquid tight)
w x d x h = 56 x 60 x 10 cm (a maximum of eight drawers is possible).
- **Additional shelf** on rails or overlays.
- **Basket** on rails
w x d x h = 60 x 65 x 10 cm.
- **Aluminium tray**
w x d x h = 60 x 65 x 2.5 cm, with rails.
- **Condensate container** can be emptied manually if no condensation is required (e.g., in an operating theatre).
- **GSM-Module** for alarm text message transmission.
- **Temperature documentation:** see detailed information on page 56.