

Basic line - glassware washer 60 cm

GW0160 (art. 860384)

€3.620,00

LABORATORY GLASSWARE WASHER

- washing up to 85 °C - antibacterial thermal disinfection
- programs: 7 default
- microprocessor electronic control
- active thermodynamic drying
- alkaline powder detergent dispenser
- peristaltic pump for acid liquid neutralizer
- washing chamber and internal door in AISI 304 stainless steel
- external panels made of AISI 304 stainless steel
- n. 2 independent washing levels through telescopic guides
- external dimensions LxDxH: 600 x 600 x 850 mm
- internal working dimensions LxDxH: 525 x 490 x 570 mm
- incorporated water softener with salt sensor
- cold water and demineralized water connections
- electronic door lock system for user safety
- electrical connection: 3/N/PE 400 V - 50 Hz - 7 kW max
- single phase version available: 1/N/PE 230 V - 50 Hz - 2,8 kW max (GW0160-1)
- 60 Hz version available
- without trolleys



OTHER POSSIBLE CONFIGURATIONS

GW0160A
(art. 860692)

LABORATORY GLASSWARE WASHER

- booster pump for non-pressure demineralized water

Machine optionals

- AS4060 - AQUA STOP WATER LEAK KIT
- B6040L - STAINLESS STEEL PLINTH FOR 60 CM MACHINES WITH LOCK
- IRCP - CEILING SPRAY ARM
- P14060 - PERISTALTIC PUMP FOR LIQUID DETERGENT
- PAD1 - BOOSTER PUMP FOR NON-PRESSURE DEMINERALIZED WATER
- PAD2 - BOOSTER PUMP FOR NON-PRESSURE DEMINERALIZED WATER
- PAD2-60 - BOOSTER PUMP FOR NON-PRESSURE DEMINERALIZED WATER
- PAD2R - PAD2 RELAY KIT
- PAD2X - ST. STEEL BOOSTER PUMP FOR NON-PRESSURE DEMINERALIZED WATER
- PAD2X-60 - BOOSTER PUMP FOR NON-PRESSURE DEMINERALIZED WATER - 60 HZ
- T6040 - STAINLESS STEEL FRAME FOR 60 CM MACHINES
- TOP60I - BUILT-IN TOP 60 CM