

Machines

Thermal washer disinfectors

Basic line - glassware washer 45 cm

GW2145 (art. 860454)

LABORATORY GLASSWARE WASHER

- washing up to 95°C - antibacterial thermal disinfection
- programs: 9 default + 6 custom
- microprocessor programmable electronic control
- serial port RS232 for connection to external printer or PC
- active thermodynamic drying
- alkaline powder detergent dispenser
- peristaltic pump for acid liquid neutralizer
- possibility of installing 1 additional peristaltic pump
- washing chamber and internal door in AISI 316L stainless steel
- external panels made of AISI 304 stainless steel
- n. 2 independent washing levels through telescopic guides
- external dimensions LxDxH: 450 x 620 x 850 mm
- internal working dimensions LxDxH: 370 x 480 x 570 mm
- incorporated water softener with salt sensor
- cold water and demineralized water connections
- electronic door lock system for user safety
- electrical connection: 1/N/PE 230 V - 50 Hz - 3,3 kW max
- 60 Hz version available
- Schuko plug 16 A - 250 V included
- upper and lower trolleys D-CS1 and D-CS2 included



OTHER POSSIBLE CONFIGURATIONS

GW2145A
(art. 860698)

LABORATORY GLASSWARE WASHER

- booster pump for non-pressure demineralized water

Machine optionals

- P12145 - PERISTALTIC PUMP FOR LIQUID DETERGENT
- PAD1 - BOOSTER PUMP FOR NON-PRESSURE DEMINERALIZED WATER
- PAD2 - BOOSTER PUMP FOR NON-PRESSURE DEMINERALIZED WATER
- PAD2-60 - BOOSTER PUMP FOR NON-PRESSURE DEMINERALIZED WATER
- PAD2R - PAD2 RELAY KIT
- PAD2X - ST. STEEL BOOSTER PUMP FOR NON-PRESSURE DEMINERALIZED WATER
- PAD2X-60 - BOOSTER PUMP FOR NON-PRESSURE DEMINERALIZED WATER - 60 HZ
- TOP45I - BUILT-IN TOP 45 CM
- WD-LS3060 - DETERGENT LEVEL SENSOR
- WD-PRINTE - EXTERNAL PRINTER

