

## Basic line - glassware washer 90 cm with drying system

### GW4190 (art. 860351)

#### LABORATORY GLASSWARE WASHER WITH DRYING SYSTEM

- washing up to 95°C - antibacterial thermal disinfection
- programs: 9 default + 6 custom
- microprocessor programmable electronic control
- serial port RS232 for connection to printer or PC
- forced hot air drying system with air filter 98% DOP
- alkaline powder detergent dispenser
- peristaltic pump for acid liquid neutralizer
- possibility of installing up to 2 additional peristaltic pumps
- washing chamber and internal door in AISI 316L stainless steel
- external panels made of AISI 304 stainless steel
- detergent cabinet made of AISI 304 stainless steel 4 x 5 liters tanks
- n. 2 independent washing levels through telescopic guides
- external dimensions LxDxH: 900 x 600 x 850 mm
- internal working dimensions LxDxH: 525 x 490 x 570 mm
- incorporated water softener with salt sensor
- cold water and demineralized water connections
- electronic door lock system for user safety
- electrical connection: 3/N/PE 400 V - 50 Hz - 7 kW max
- single phase version available: 1/N/PE 230 V - 50 Hz - 2,8 kW max (GW4190-1)
- 60 Hz version available
- without trolleys



#### OTHER POSSIBLE CONFIGURATIONS

##### GW4190A (art. 860711)

#### LABORATORY GLASSWARE WASHER WITH DRYING SYSTEM

- booster pump for non-pressure demineralized water

##### GW4190C (art. 860353)

#### LABORATORY GLASSWARE WASHER WITH DRYING SYSTEM

- high efficiency steam condenser Ecoslim, with cold water injection

##### GW4190CA (art. 860712)

#### LABORATORY GLASSWARE WASHER WITH DRYING SYSTEM

- high efficiency steam condenser Ecoslim, with cold water injection
- booster pump for non-pressure demineralized water



**VONMARCKEN**  
LABORATORY & MEDICAL EQUIPMENT

### Machine optionals

- AF4060 - ABSOLUTE HEPA FILTER
- AS4190 - AQUA STOP WATER LEAK KIT
- B9040L - STAINLESS STEEL PLINTH FOR 90 CM MACHINES WITH LOCK
- FLUX4060 - DOSING CONTROL FOR ADDITIONAL PERISTALTIC PUMPS
- IRCP - CEILING SPRAY ARM
- P14060 - PERISTALTIC PUMP FOR LIQUID DETERGENT
- P14190 - PERISTALTIC PUMP FOR LIQUID DETERGENT
- P34190 - PERISTALTIC PUMP FOR LIQUID ADDITIVES
- P44190 - PERISTALTIC PUMP FOR LIQUID ANTIFOAM
- PAD1 - BOOSTER PUMP FOR NON-PRESSURE DEMINERALIZED WATER
- PAD2 - BOOSTER PUMP FOR NON-PRESSURE DEMINERALIZED WATER
- PAD2-60 - BOOSTER PUMP FOR NON-PRESSURE DEMINERALIZED WATER
- PAD2R - PAD2 RELAY KIT
- PAD2X - ST. STEEL BOOSTER PUMP FOR NON-PRESSURE DEMINERALIZED WATER
- PAD2X-60 - BOOSTER PUMP FOR NON-PRESSURE DEMINERALIZED WATER - 60 HZ
- T9040 - STAINLESS STEEL FRAME FOR 90 CM MACHINES
- TANKBSK - UPPER LEVEL CAN HOLDER BASKET
- TOP90IB - BUILT-IN TOP 90 CM
- TRACELOG - REMOTE CONTROL AND TRACEABILITY SOFTWARE
- WD-LANE - DATA COMMUNICATION CARD
- WD-LS4190 - DETERGENT LEVEL SENSOR
- WD-PRINT9 - PANEL PRINTER