

TEMPSEN



monitoring for
Life Science



DS-A-140906 Rev. B

Alpha TD80

Dry Ice Probeless USB PDF Data Logger



Auto PDF Report with Embedded Data

Automatically generating encrypted PDF format report, no software required to obtain data, embedded raw data allows analyzing report via TempCentre and Cold Chain Cloud.



Online configuration without software

In support of online configuration without needing to download and install any specific software.



Repeat Start

Repeat start function enables quick start on site without re-configuration .



Mark Function

Click Mark button to write in time stamp for events requiring special attention during shipment, up to 9 marks available.




3-point Calibration

Factory 3-point calibration, each logger comes with a NIST traceable calibration certificate.



TempCentre 2 Support

Work with TempCentre 2 desktop software to easily and accurately view, analyze, archive and share data recorded from transport and storage, and achieve 21 CFR 11 compliance.



Multiple Alarm Ranges

Up to 5 alarm ranges offer precise and intuitive statistics for each configured alarm range.

Type	Multi-use
Sensor	Temperature: Internal RTD Sensor
Memory Capacity	14400 readings
Measurement Range	-80°C...70°C (-112°F...158°F)
Accuracy	±0.5°C / 0.9°F
Resolution	0.1°C / °F
Start Mode	Manual / Auto start
Logging Interval	1 minute...2 hours
Alarm Range	High and low alarm / 5 alarm ranges
Battery	3.6V lithium battery
Run Time	120 days (60 days@-80°C)
Shelf Life	2 years
Display	Multi-function LCD <ul style="list-style-type: none"> •OK(✓), Alarm(x), Running status •Temperature statistics (max, min, avg) •Limit violation event indication •Duration time of each alarm zone •Mark history •Remaining battery days
Button	Start / Stop / Mark / View
Connection	USB 2.0 Connector
Data Specification	<ul style="list-style-type: none"> •Temperature •Date/Time •Mark
Automatic Data File	Encrypted PDF report with embedded raw data
Software	TempCentre 2 (21 CFR 11 compliant)
Compatible OS	WIN 7 / 8 / 10
Calibration	Factory NIST traceable 3-point calibration
Certifications	CE, DO160G, RoHS
Dimensions	107mm L x 56mm W x 18mm H
Weight	Approx. 80g
Packaging/Material	Case / Polycarbonate
Protection Class	IP54