




BIOMEDICAL

ULTF 500

ULT TECHNICAL SPECIFICATIONS



Color code handle	RAL 9003
Color code housing	RAL 9003

Product Type	ULT (230V)
Brand name on Product	Vestfrost Solutions

PERFORMANCE DATA TEMPERATURE	
Temperature range [°C]	-90...-40
Temperature variation at -80 °C [± K]	2.5
Temperature fluctuation at -80 °C [± K]	1.5
Cooling down time (min) from 22 °C to -80 °C	360
Warm-up time during power failure from -80 °C / -122 °F to -60 °C / -76 °F [min]	230

ELECTRICAL DATA	
Rated Voltage [V]	230
Power frequency [Hz]	50
Nominal power [kW]	1.6
Unit fuse [A]	10
Power plug standard	2m C13 CEE 7/7
Phase (Nominal voltage)	1~

MEASURES	
Interior volume [L]	477
Net weight of the unit (empty) [kg]	247
Permitted load [kg]	200
Permitted load of individual compartment (kg)	50
Wall clearance back [mm]	100
Wall clearance sidewise [mm]	250
Mobility	4 wheels, 2 w. lock

INTERNAL DIMENSIONS	
Interior width [mm]	606
Interior height [mm]	1300
Interior depth [mm]	605

DOORS	
Inner doors	2
Unit doors	1

HOUSING DIMENSIONS NOT INCL. FITTINGS AND CONNECTIONS	
Width net [mm]	826
Height net [mm]	1966
Depth net [mm]	938



BIOMEDICAL

ULTF 500

ULT TECHNICAL SPECIFICATIONS

ENVIRONMENT SPECIFIC DATA

Energy consumption at set-point -80 °C (kWh/24h)	7,9
Average heat dissipation at set-point (-80°C, Amb. 20°C)(W)	330
Sound-pressure level [dB(A)]	47

FIXTURES

Number of shelves (std./max.)	3/13
-------------------------------	------

LOAD-VARIANTS

Freezer racks per compartment	4
Cryoboxes, 50 mm	352

FEATURES

Alarm system, batterybacked	standard
Foam filled compartment door	standard
Battery back-up system (CO2)	standard
Shipping pallet (extra specified pallet)	option (no additional article numbers; only on request)

ACCESSORIES

5m power cable	C 13 BS 1363 British plug – 5023-0285
	C 13 CEE 7/7 European plug – 5023-0283
	C 13 type 13 Swiss plug – 5023-0284
Deicing kit consisting of de-icing tray, wiper and scraper	8012-1900
Grid shelf – For temperature range -40 °C to -60 °C, 3 provided in set, including shelf supports	8012-1903
Shelf, incl. shelf supports, stainless steel	8012-1901
WLAN kit, wireless connection between ULT units and APT-COM4, LIMS or customer solution.	8012-2262

STANDARDS & APPROVALS

Energy Star certified (3rd part)	yes
Machinery directive (EN ISO 12100, EN ISO 13732-3, EN60204-1)	yes
Applied voluntarily: EN61010-1, EN61010-2-11(if wished, this could also be listed in the CE DoC)	
Electromagnetic Compability Directive 2014/30/EU (EN 61326-1)	yes
RoHS Directive (EN IEC 63000:2018)	
Compliant with DIN 13277	Only partly. ULTs are validated referring to DIN DIN 12880; 2007-05

LABORATORY TEST MEASUREMENTS

Pull down	360 min
Noise level	47dBA
Warm-up time by power failure	250 min
Temperature variation	2,5 K
Temperature fluctuation	1,5 K
Energy consumption	7,9 kW/24h




BIOMEDICAL

ULTF 500

ULT TECHNICAL SPECIFICATIONS

SELLING POINTS

Lowest energy consumption in its class	7,9
Environmentally-friendly refrigerants	R290/R170
Thermal insulation with unique long-life VIPs	vacuum insulation panels
Rust proof interior	Stainless steel 1.4016 grade
Individual safety concept	option
Temperature range [°C]	-90 °C to -40 °C
Compressor cooling	cascade
Innovative door gasket	reduce ice built-up
Detachable inner doors	stainless steel
Zero-voltage alarm contact	in-house alarm system
Internal data logger	USB read out
Ethernet interface	yes
Access ports	2x Ø28mm rear
Shipping pallet	without forklift
Packaging	Recyclable
Powder-coating	Solvent free



Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

A/S Vestfrost | Falkevej 12 | DK-6705 Esbjerg Ø | www.vestfrostsolutions.com

VESTFROST
SOLUTIONS