

Klik hier voor meer informatie op vonmarcken.nl

PRODUCT

The VTS 1365 is developed for reliable storage in pharmacies, laboratories and hospitals.

The unit is equipped with external digital temperature display and fully electronic temperature control that ensures a set temperature between -5°C to -25°C.

SPECIFICATIONS

Gross volume, litres (cu. ft.)	1.500 (52.97)
Internal storage capacity, litres (cu. ft.)	1.365 (48.20)
Temperature range (25°C AMB)	-5°C to-25°C
Temperature probes	2
Compressor	Hermetic
Refrigerant	R404a
Noise level, dB	52
Power consumption @ 25°C AMB, kWh / 24h	9,50
Power consumption, kWh / year	3.468
Voltage, V	115/230V
Frequency, Hz	50

FEATURES

Certifications	CB, CE & EMC
No. of wire shelves	6 (12)
Defrost	Automatic
Battery Backup	N/A
USB	N/A
Data connection	N/A
Digital controller	YES
Data logging, # logs	10
Analogue chart recorder	Optional
Alarm relay	N/A

VTS 1365 LOW TEMPERATURE FREEZER



DIMENSIONS

Height, mm (inches)	2.100 (82.67)
Height w. castors, mm (inches)	N/A
Width, mm (inches)	1.500 (59.05)
Depth, mm (inches)	820 (32.28)
Gross weight, kg (lbs)	285 (629)
Net weight, kg (lbs)	255 (563)

LOADING QUANTITIES

Qty. per 20' / 40' container	6 / 14
Qty. per truck (EU standard)	16



VONMARCKEN

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

