

Klik hier voor meer informatie op vonmarcken.nl

PRODUCT

The VTS 625 is developed for reliable storage in pharmacies, laboratories and hospitals.

The unit is equipped with external digital temperature display and fully electronic temperature control that ensures a set temperature between -5°C to -25°C.

SPECIFICATIONS

Gross volume, litres (cu. ft.)	700 (24.72)
Internal storage capacity, litres (cu. ft.)	625 (22.07)
Temperature range (25°C AMB)	-5°C to-25°C
Temperature probes	2
Compressor	Hermetic
Refrigerant	R404a
Noise level, dB	50
Power consumption @ 25°C AMB, kWh / 24h	8,10
Power consumption, kWh / year	2.957
Voltage, V	115/230V
Frequency, Hz	50

FEATURES

ons CB, CE &	k EMC
e shelves 3	
Autom	atic
ickup N/A	A
N/A	A
ection N/A	A
troller YES	6
ng, # logs 10	
chart recorder Optio	nal
y N/A	A.
ng, # logs 10 chart recorder Optio	nal

VTS 625 LOW TEMPERATURE FREEZER



DIMENSIONS

Height, mm (inches)	2.100 (82.67)
Height w. castors, mm (inches)	N/A
Width, mm (inches)	750 (29.52)
Depth, mm (inches)	820 (32.28)
Gross weight, kg (lbs)	190 (419)
Net weight, kg (lbs)	170 (375)

LOADING QUANTITIES

Qty. per 20' / 40' container	12 / 26
Qty. per truck (EU standard)	30



Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.



VON MARCKEN